

Safety Data Sheet
Xylene

Version 2.5

Revision Date: 03/27/2018

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Xylene

Recommended use of the chemical and restrictions on use

Recommended use : Solvent.

Manufacturer or supplier's details

Company : Nexeo Solutions, LLC.
Address : 3 Waterway Square Place Suite 1000
The Woodlands, TX. 77380
United States of America

Emergency telephone number:

Health North America: 1-855-NEXEO4U (1-855-639-3648)

Health International: 1-855-NEXEO4U (1-855-639-3648)

Transport North America: CHEMTREC (1-800-424-9300)

Additional Information: : Responsible Party: Product Safety Group
E-Mail: msds@nexeosolutions.com
SDS Requests: 1-855-429-2661
SDS Requests Fax: 1-281-500-2370
Website: www.nexeosolutions.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Acute toxicity (Inhalation) : Category 4

Acute toxicity (Dermal) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

GHS Label element

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.
H312 + H332 Harmful in contact with skin or if inhaled
H315 Causes skin irritation.
H319 Causes serious eye irritation.

Precautionary statements : **Prevention:**
P210 Keep away from heat/sparks/open flames/hot surfaces.

TTB Distribution, Inc
4206 S. General Bruce Dr.
Temple, Tx 76502-4836
(254) 778-8701
Received: 4-3-18

Safety Data Sheet
Xylene

Version 2.5

Revision Date: 03/27/2018

No smoking.
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Hazardous components

CAS-No.	Chemical Name	Weight %
1330-20-7	Mixed xylenes	90 - 100
100-41-4	**Ethylbenzene	0 - 35
98-82-8	**Cumene	0.1 - 1

Any Concentration shown as a range is due to batch variation.

Special Notes: : ** Other substances in the product which may present a health or environmental hazard.

SECTION 4. FIRST AID MEASURES

Safety Data Sheet
Xylene

Version 2.5

Revision Date: 03/27/2018

- | | |
|-------------------------|---|
| General advice | : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended. |
| If inhaled | : Consult a physician after significant exposure.
If unconscious place in recovery position and seek medical advice. |
| In case of skin contact | : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes. |
| In case of eye contact | : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist. |
| If swallowed | : Keep respiratory tract clear.
Do not induce vomiting without medical advice.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital. |

SECTION 5. FIREFIGHTING MEASURES

- | | |
|---|---|
| Suitable extinguishing media | : Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
| Unsuitable extinguishing media | : High volume water jet |
| Specific hazards during fire-fighting | : Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).
Aldehydes |
| Further information | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers. |
| Special protective equipment for firefighters | : Wear self-contained breathing apparatus for firefighting if necessary.
Use personal protective equipment. |

Safety Data Sheet

Xylene

Version 2.5

Revision Date: 03/27/2018

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Safety Data Sheet
Xylene

Version 2.5

Revision Date: 03/27/2018

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis		
1330-20-7	Mixed xylenes	TWA	100 ppm	ACGIH		
		STEL	150 ppm	ACGIH		
		TWA	100 ppm 435 mg/m ³	OSHA Z-1		
		TWA	100 ppm	ACGIH		
		STEL	150 ppm	ACGIH		
100-41-4	**Ethylbenzene	TWA	20 ppm	ACGIH		
		TWA	100 ppm 435 mg/m ³	NIOSH REL		
		ST	125 ppm 545 mg/m ³	NIOSH REL		
		TWA	100 ppm 435 mg/m ³	OSHA Z-1		
		TWA	100 ppm 435 mg/m ³	OSHA P0		
		STEL	125 ppm 545 mg/m ³	OSHA P0		
		98-82-8	**Cumene	TWA	50 ppm	ACGIH
				TWA	50 ppm 245 mg/m ³	NIOSH REL
TWA	50 ppm 245 mg/m ³			OSHA Z-1		
TWA	50 ppm 245 mg/m ³			OSHA P0		

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Safety Data Sheet

Xylene

Version 2.5

Revision Date: 03/27/2018

- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : Clear, Colorless
- Odour : aromatic, Hydrocarbon-like, sweet
- Odour Threshold : No data available
- pH : No data available
- Freezing Point (Melting point/freezing point) : -48 - -26.15 °C (-54 - -15.07 °F)
- Boiling Point (Boiling point/boiling range) : 137 - 139 °C (279 - 282 °F)
- Flash point : 27 °C (81 °F)
Method: closed cup
- Evaporation rate : 0.8
(Butyl Acetate = 1)
- Flammability (solid, gas) : No data available
- Upper explosion limit : 7 %(V)
- Lower explosion limit : 1 %(V)
- Vapour pressure : 6 - 7 mmHg @ 20 - 25 °C (68 - 77 °F)
- Relative vapour density : 3.7 @ 20 - 25 °C (68 - 77 °F)
(Air = 1.0)
- Relative density : 0.86 - 0.88 @ 20 - 25 °C (68 - 77 °F)
Reference substance: (water = 1)
- Density : 0.87 g/cm³ @ 20 - 25 °C (68 - 77 °F)
- Solubility(ies)
Water solubility : slightly soluble
- Solubility in other solvents : No data available

Safety Data Sheet

Xylene

Version 2.5

Revision Date: 03/27/2018

Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	432 - 530 °C
Thermal decomposition	:	No data available
Viscosity	:	
Viscosity, kinematic	:	0.717 - 0.864 mm ² /s @ 20 °C (68 °F)

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Vapours may form explosive mixture with air.
Conditions to avoid	:	Keep away from heat, flame, sparks and other ignition sources. Exposure to sunlight. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	:	Strong oxidizing agents Strong acids Nitrogen oxides (NO _x) Alkalis Plastics Reducing agents
Hazardous decomposition products	:	Carbon oxides Hydrocarbons Aldehydes

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Components:

1330-20-7:

Acute inhalation toxicity	:	LC50 (Rat, male): 6700 ppm Exposure time: 4 h Assessment: The component/mixture is moderately toxic after short term inhalation.
---------------------------	---	--

Safety Data Sheet
Xylene

Version 2.5

Revision Date: 03/27/2018

Acute dermal toxicity : LD50 (Rabbit): 1,700 mg/kg
Assessment: The component/mixture is moderately toxic after single contact with skin.

Skin corrosion/irritation

Components:

1330-20-7:

Species: Rabbit

Exposure time: 24 h

Result: Irritating to skin.

Serious eye damage/eye irritation

Components:

1330-20-7:

Species: Rabbit

Result: Irritating to eyes.

Carcinogenicity

Product:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

IARC

Group 2B: Possibly carcinogenic to humans

100-41-4

**Ethylbenzene

98-82-8

**Cumene

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

ACGIH

Confirmed animal carcinogen with unknown relevance to humans

100-41-4

**Ethylbenzene

Reproductive toxicity

Product:

Reproductive toxicity - Assessment

Clear evidence of adverse effects on sexual function and fertility, based on animal experiments.

Safety Data Sheet

Xylene

Version 2.5

Revision Date: 03/27/2018

STOT - single exposure

Product:

Target Organs: Respiratory system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

Product:

Target Organs: Auditory system

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Components:

98-82-8:

Partition coefficient: n-octanol/water : log Pow: 3.55 (23 °C)

Mobility in soil

No data available

Safety Data Sheet

Xylene

Version 2.5

Revision Date: 03/27/2018

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.
For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact NEXEO's Environmental Services Group at 800-637-7922.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

DOT (Department of Transportation):
UN1307, XYLENES, 3, III

IATA (International Air Transport Association):
UN1307, XYLENES, 3, III

IMDG (International Maritime Dangerous Goods):
UN1307, XYLENES, 3, III, Flash Point:27 °C(81 °F)

SECTION 15. REGULATORY INFORMATION

WHMIS Classification : B2: Flammable liquid
D2A: Very Toxic Material Causing Other Toxic Effects
D2B: Toxic Material Causing Other Toxic Effects

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Safety Data Sheet
Xylene

Version 2.5

Revision Date: 03/27/2018

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
**Ethylbenzene	100-41-4	1000	2857
Mixed xylenes	1330-20-7	100	100

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard
Chronic Health Hazard

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

100-41-4 **Ethylbenzene

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

1330-20-7 Mixed xylenes
100-41-4 **Ethylbenzene

Clean Water Act

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307

100-41-4 **Ethylbenzene

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

1330-20-7 Mixed xylenes
100-41-4 **Ethylbenzene
108-88-3 **Toluene
71-43-2 **Benzene
91-20-3 **Naphthalene

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

1330-20-7 Mixed xylenes
100-41-4 **Ethylbenzene
108-88-3 **Toluene
71-43-2 **Benzene
91-20-3 **Naphthalene

Massachusetts Right To Know

1330-20-7	Mixed xylenes	90 - 100 %
100-41-4	**Ethylbenzene	0 - 35 %
71-43-2	**Benzene	0 - 0.1 %

Pennsylvania Right To Know

1330-20-7	Mixed xylenes	90 - 100 %
100-41-4	**Ethylbenzene	0 - 35 %
98-82-8	**Cumene	0.1 - 1 %
108-88-3	**Toluene	0.1 - 1 %
71-43-2	**Benzene	0 - 0.1 %

New Jersey Right To Know

1330-20-7	Mixed xylenes	90 - 100 %
100-41-4	**Ethylbenzene	0 - 35 %

Safety Data Sheet

Xylene

Version 2.5

Revision Date: 03/27/2018

108-88-3

**Toluene

0.1 - 1 %

California Prop 65

WARNING! This product contains a chemical known to the State of California to cause cancer.

100-41-4

**Ethylbenzene

98-82-8

**Cumene

71-43-2

**Benzene

91-20-3

**Naphthalene

WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

108-88-3

**Toluene

71-43-2


**Benzene

The components of this product are reported in the following inventories:

- TSCA : On TSCA Inventory
- DSL : All components of this product are on the Canadian DSL
- AICS : On the inventory, or in compliance with the inventory
- NZIoC : On the inventory, or in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PHIL : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

NFPA:



Special hazard.

HMIS III:

HEALTH	2*
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we

Safety Data Sheet

Xylene

Version 2.5

Revision Date: 03/27/2018

do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by NEXEO™ Solutions EHS Product Safety Department (1-855-429-2661) MSDS@nexeosolutions.com.

Revision Date : 03/27/2018

Legacy SDS: : 100000027727

Material number:

16127723, 16127029, 16118414, 16116444, 16116443, 16109065, 779350, 16063696, 102351, 776944, 763953, 710729, 710728, 708716, 707260, 706448, 638918, 568063, 554061, 554060, 554200, 508616, 508582, 508489, 70145, 70881, 70227, 70442, 53546, 70136, 87256, 53755, 103201, 85972, 103204, 86307, 102898, 69592, 70082, 85965, 54057, 70432, 86513, 102683, 102433, 86815, 103194, 508229, 508294, 508230, 39908, 22253, 22252, 22033, 22034, 20526, 20524, 16066675, 16061583, 16066710, 16084135, 16075696, 16056826, 16056828, 16056827, 16056829, 16056825, 16041807, 16040131, 16036781, 16017302, 16005979, 781040, 102986, 102359, 86304, 53758, 102348, 69917, 502710, 20530, 20529, 20528, 20525, 20523, 20522

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological

Safety Data Sheet
Xylene

Version 2.5

Revision Date: 03/27/2018

			Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50		Lethal Concentration 50%	